Scopia XT4200 Cost-Effective HD Video Communication







Efficient HD Performance

The Scopia XT4200 delivers efficient HD performance featuring H.264 High Profile for bandwidth efficiency and H.264 SVC for high quality images, even in unpredictable network environments. The XT4200 also offers dual 720p 60fps live HD video and HD content, HD audio and optional iPad Multi-Touch control.



Outstanding Value

The Scopia XT4200 is well-equipped and offers outstanding value including many features that are either unavailable or costly upgrades in other vendor offerings. Dual 720p 60fps HD video, H.264 High Profile, H.264 SVC, dual display support, wide angle PTZ camera – are all included for cost-effective video communications deployment.



Intuitive and Easy-to-Use

The Scopia XT4200 user interface is designed to deliver a simplified end-user experience. It leverages design principles of Radvision's award-winning iPad and iPhone applications and enables instant, intuitive and effective control - no training required. For an enhanced user experience, the XT4200 is available with optional Multi-Touch control via the Apple iPad.



Sleek and Elegant Design

The Scopia XT4200's refinement and polish go beyond the user experience to the sleek and elegant hardware design of the system. The XT4200 is a natural fit for today's businesses, not only for its ease of use, but also its modern design that complements a conference room. Finally a powerful business system to put on display and not hide in the closet.



Integrated Total Solution

The Scopia XT4200 room system complements Radvision's total video conferencing solution including the VC240 executive HD desktop system, Scopia Desktop and Scopia Mobile for users on-the-go, Scopia Elite for multi-party communications and Scopia iVIEW Management Suite. Scopia solutions also offer integration with UC solutions from Avaya and others.

Scopia XT4200 Specifications

Communications

- IP: H.323, SIP (RFC 3261)
- ISDN¹ Supported through Scopia Gateway
- Bit rate: H.323, SIP: up to 4/6¹ Mbps H.320: up to 2 Mbps
- MCU compatibility: H.243, H.231

Video

- 2 simultaneous 720p 60fps channels: camera + content
- H.263, H.263+, H.263++, H.264, H.264 High Profile, H.264 SVC (both using Baseline and High Profile)
- Dual video: H.239 (H.323); BFCP (SIP)
- HDMI input formats 1920 x 1080 @ 25, 30, 50, 60fps 1280 x 720 @ 25, 30, 50, 60fps 720 x 576 @ 50fps 720 x 480 @ 60fps 640 x 480 @ 60fps
- Live video encoding formats 1280 x 720 @ 25, 30, 50, 60fps: HD720p 25, 30, 50, 60fps 1024 x 576 @ 25, 30fps: w576p 768 x 448 @ 25, 30fps: w448p 704 x 576 @ 25, 30fps: 4CIF 704 x 480 @ 25, 30fps: 4SIF 576 x 336 @ 25, 30fps
- 512 x 288 @ 25, 30fps: wCIF
- 400 x 224 @ 25, 30fps
- 352 x 288 @ 25, 30fps: CIF
- 352 x 240 @ 25, 30fps: SIF
- DVI input formats 1920 x 1080 @ 25, 30, 50, 60fps 1440 x 900 @ 60fps: WSXGA 1280 x 1024 @ 60fps: SXGA 1280 x 720 @ 25, 30, 50, 60fps 1280 x 768 @ 60fps: WXGA 1024 x 768 @ 60fps: XGA 800 x 600 @ 60fps: SVGA 640 x 480 @ 60fps: VGA
- PC content encoding formats: Same as DVI input formats @ 60fps (scaled to 720p 60fps when exceeding such resolution)
- HDMI output formats 1280 x 720 @ 50, 60fps

Camera

- Resolution: 720p 60fps
- Presets: . 122 16° - 70° .
- Field of View (H): PAN / Tilt: ± 100° / ± 25°
- Zoom (standard):
- 5x (optical) Zoom (optional):
- 10x optical, 4x digital, 40x total

Analog/Optical Audio

 \bigcirc

EMEA

+

unique technologies that harness the power of video, voice, and data over any network. www.radvision.com

Information contained in this document is subject to change without notice. This document is not part of a contract or license as may be expressly agreed. Radvision is a registered trademark of Radvision Ltd an Avaya Company. All product and company names herein may be trademarks of their registered owners. All rights reserved © 2012 Radvision Ltd an Avaya Company.All rights reserved © 2012 Radvision Ltd an Avaya Company.

T +44 20 3178 8685

F +44 20 3178 5717

infoUK@radvision.com

(()

* Images of Scopia XT4200 components may vary from the actual product.

• Far End Control: H.224, H.281

12V === 5A

0

About Radvision

USA/Americas

T +1 201 689 6300

F +1 201 689 6301

infoUSA@radvision.com

Audio

- Acoustic echo cancellation
- Adaptive post filtering
- . Audio error concealment
- Automatic Gain Control (AGC) Automatic noise suppression

	Frequency response:	
	G.711:	300 – 3,400 Hz
	G.728:	50 – 3,400 Hz ¹
	G.729A:	50 – 3,400 Hz ¹
	G.722:	50 – 7,000 Hz
	G.722.1:	50 – 7,000 Hz
	G.722.1 Annex C:	50 – 14,000 Hz
	AAC-LD:	50 – 14,000 Hz
	G.719:	50 – 20,000 Hz

Microphone 180° range

- Frequency response: 50 20,000 Hz
- Audio/Video Interfaces

Video inputs:

- 1 x HDMI
- 1 x DVI-I
- Video outputs:
- 2 x HDMI for dual display
- Audio inputs:
- 1 x HDMI

1 x Microphone Pod (RJ-11) 1 x 3.5 mm (1/8") line in jack for audio source (analog / digital with mini-TOSLINK adapter)

• Audio outputs: 1 x HDMI

1 x 3.5 mm (1/8") line out jack (analog / digital with mini-TOSLINK adapter)

Network Features

- IPv4 and IPv6 simultaneous support
- Auto Gatekeeper discovery
- QoS support: IP Precedence, IP Type of Service (ToS), Differentiated Services (diffserv)
- IP adaptive packet management including Flow control Packet Loss based down-speeding
- Packet Loss recovery policies
- DTMF tones: H.245, RFC2833
- SNTP date and time synchronization
- **Network Protocols** TCP/IP, TELNET, HTTP, HTTPS, DNS, DHCP, RTP/RTCP, STUN, SNTP, TFTP
- Network Interfaces
- 2 x 10/100/1000 Base-T full-duplex (RJ-45). (2nd GLAN is optional)

Ē

Radvision, an Avaya company, is a leading provider of video conferencing and telepresence technologies over IP and wireless networks. We offer end-to-end visual communications that help businesses collaborate more efficiently. Together, Radvision and Avaya are propelling the unified communications evolution forward with

T +852 3472 4388

F +852 2801 4071

infoAPAC@radvision.com

APAC

0(******)0

Firewall Traversal

0

- Auto NAT discovery HTTP and STUN
- H.460.18, H.460.19
- "Keep Alive" packet time configurable

Camera Interface

VISCA RS232 for PTZ control (Mini-DIN 8-pin)

User Interface

- 21 language on-screen user interface
- Infrared remote control
- API for endpoint control
- Scopia Control application for Apple iPad¹ Directory Service & Address Book

LDAP Client (H.350)

Receive global address book from LDAP Server including Scopia iVIEW

Security Features

- Embedded encryption²
 - Key generation and exchange with Public-Key Cryptography (Diffie-Hellman), (H.323, SIP)
 - H.235 AES 128 Confidentiality for RTP media
- H.235 MD5 Authentication
- H.235 Authentication and Integrity (H.235v3/ Annex D)
- **Digest Authentication**
- Microsoft NTLM Authentication and Session
- Security (SSP) HTTPS, SSH
- Selective enable / disable of IP features
- Web Management
- Configuration, call, diagnostics and management functions are accessible with: Internet Explorer 7.0+, Firefox 3.0+, Safari 3.0+, Chrome 16.0+

Options

- 40x Zoom upgrade (10x optical, 4x digital)
- Scopia Control application for Apple iPad
- 2nd GLAN
- Extended IP bit rate (up to 6Mbps)
- Advanced Audio Codec Pack (G.728 and G.729A)
- Digital 3-way microphone POD
- **Power Supply**
- 100 240 VAC, 50-60 Hz, 2.5 A Max.

15.2 cm (6.0")

13.5 cm (5.3")

12.0 cm (4.7")

Radvision representative for details.

Encryption is subject to local regulations and in some countries is restricted or limited. Please contact your

554 D

R\DVISION[®]

an Avaya company

01-MKT-DH-1112-EN-C

- **Physical Characteristics**
- Horizontal / Vertical Mounting: Ŵ 29 cm (11.4")
- 16.5 cm (6.5") D٠
- Н· 4 cm (1.6")
- Weight: 2.4 kg (5.3 lb)

Weight: 1.6 kg (3.5 lb)

Weight: 0.4 kg (0.9 lb)

고윤

Camera:

H:

D

W:

2 중동

2

Optional

W 25.0 cm (9.8")

Microphone Pod